



FEATURES

INTENDED USE – Light engine delivers long life to ensure a sound quality, low-maintenance light installation.

CONSTRUCTION – Metal parts are die formed from code-gauge steel. Prismatic diffuser is 100% acrylic with sonically welded luminous ends.

FINISH – Five-stage iron phosphate pretreatment assures superior paint adhesion and rust resistance.

OPTICS – Curved prismatic diffuser with linear side prisms and highly transmissive overlay minimizes lamp image.

ELECTRICAL – Long-life LEDs, coupled with high-efficiency drivers, provide extended service life at 50,000 hours.

APPLICATION – Surface mounted luminaire is well suited for use on concrete, plaster, and drywall ceilings in residential and commercial buildings. It provides maximum light output with minimum clearance.

EVEN LIGHT DISTRIBUTION – Full length U-shaped prismatic acrylic diffusers provide even light distribution.

SPECIFICATIONS

Specs	Model No. LEW38UNV
	38W 48" LED surface mount wrap
Size	48.6" x 6.7" x 2.4"
Weight	6 lbs
Lumen	3500 lm
Light Efficacy	88 Lm/W
Color(CCT)	5000K
CRI	>80
Beam Angle	110°(attached light distribution)
Working Temperature	-20°C ~ +40°C
Safety	Class II
Driver	Inside
Input Voltage	100-277V AC
Frequency	50/60Hz
Power	38W
Efficiency	86%
PF	0.90
Max THD	20%
Control/Dim Type	0-10V dim
Dim Range	10%-100%
L70 Lifespan	50000H
Warranty	5 year
IES file	Yes